

4H Cartridge

Delivers premium quality water for hot cup vending applications



4H Replacement Cartridge: EV9610-00 (1 pack) EV9611-00 (6 pack)

BENEFITS

Provides clear, fresh, premium quality ingredient water for great tasting hot beverages

Everpure's unique filter blend using activated carbon reduces chlorine taste and odor and other offensive contaminants

Saves energy by reducing scale build-up. Proportioned scale inhibitor feed dramatically prevents limescale from forming in equipment

Engineered to always feed the correct amount of scale inhibitor into each volume of water

Precoat submicron technology reduces dirt and particles as small as I/2 micron in size

Reduces health contaminants such as asbestos fibers and Cryptosporidium and Giardia cysts

Does not remove fluoride

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

NSF Certified under NSF/ANSI Standards 42 and 53

INSTALLATION TIPS

Never use saddle valve for connection

Use 3/8" water line

Install vertically with cartridge hanging down

Allow 2-1/2" clearance below the cartridge for easy cartridge replacement

Flush 4H cartridge by running water through filter for three minutes at full flow

OPERATION TIPS

Change cartridges on a regular 6 month preventative maintenance program

Change cartridges when capacity is reached or when pressure falls below 10 psi

Service flow rate must not exceed 0.5 gpm

Always flush the filter cartridge at time of installation and cartridge change

APPLICATION/SIZING

For hot cup vending machine applications

Rated Capacity: 3,000 gallons (11,350L)

SPECIFICATIONS

Overall Dimensions: 14.5"H x 3.25"Diameter

Service Flow Rate: Maximum 0.5 gpm (1.9 Lpm)

Rated Capacity: 3,000 gallons (11,350L)


Pressure Requirements: 10 psi -125 psi (0.7 – 8.6 bar), non-shock

Maximum Temperature: 35°F - 100°F (2-38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

4H Cartridge



WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects
Chemical Unit
Taste and Odor Reduction
Chlorine Reduction
Mechanical Filtration Unit
Particulate Reduction, Class I:
99.9+% reduction of particles
one-half micron and larger in size

Standard No. 53: Health Effects Mechanical Filtration Unit Cyst Reduction

Distributed by:



Andrew's Water Treatment Ltd 47-49 Kensington Road, Southport PR9 0RY

Tel: 01704 531 556 http://www.andrewswater.co.uk office@andrewswatertreatment.co.uk