



EV9612-56

# MC<sup>2</sup> Filter Cartridge

Delivers premium quality water for fountain and combination applications



MC<sup>2</sup> Replacement Cartridge: EV9612-56

## BENEFITS

New and improved Micro-Pure II media with AgION™ antimicrobial protection inhibits any potential bacterial growth

Reduces chlorine taste and odor and other offensive contaminants that can adversely affect the taste of beverages

Improves the taste of fountain beverages and helps retain the drink's carbonation

Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size and possible health contaminants such as asbestos fibers and Cryptosporidium and Giardia cysts

Protects drink system seals, pump, tubing and small orifices from clogging, corrosion and abrasive wear

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

NSF Certified under NSF/ANSI Standards 42 and 53

## INSTALLATION TIPS

Install vertically with cartridge hanging down

Allow 2-1/2" clearance below the cartridge for easy cartridge replacement

Flush cartridge by running water through system for five minutes at full flow

## OPERATION TIPS

Change cartridges on a regular 6 month preventative maintenance program

Change cartridges when capacity is reached or when pressure falls below 10 psi

Always flush the filter cartridge at time of installation and cartridge change

## APPLICATION/SIZING

For fountain beverage applications

For combination system applications

Rated Capacity: 9,000 gallons (34,068L)

# MC<sup>2</sup> Filter Cartridge

## SPECIFICATIONS

Overall Dimensions:  
20.75"H x 3.25"Diameter

Service Flow Rate:  
Maximum 1.67 gpm (6.3 Lpm)


Rated Capacity: 9,000 gallons

Pressure Requirements:  
10 - 125 psi (0.7 – 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



## WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects  
Chemical Unit  
Taste and Odor Reduction  
Chlorine Reduction  
Mechanical Filtration Unit  
Nominal Particulate Reduction,  
Class 1: 99.2% reduction of particles  
one-half micron and larger in size

Standard No. 53: Health Effects  
Mechanical Filtration Unit  
Turbidity Reduction  
Cyst Reduction  
Asbestos Reduction

Distributed by:

**Andrew's**  
Water Treatment

Andrew's Water Treatment Ltd  
47-49 Kensington Road,  
Southport  
PR9 0RY

Tel: 01704 531 556  
<http://www.andrewswater.co.uk>  
[office@andrewswatertreatment.co.uk](mailto:office@andrewswatertreatment.co.uk)